



Wire rope Dyform 34LR

Product information



Very Low Rotation.
Superior bending fatigue life when compared with conventional low rotation ropes.
Excellent resistance to crushing and abrasion particularly on multi layer drums resulting from the compacted strands.
Reduced elongation results from increased steel content and the Dyform process.

ISO 4309 Rope Category No: 10-40mm RCN.23-2, 42-76mm RCN.31

Features: Extremely strong low rotation Crane Hoist Rope.

Material: High Carbon Steel

Marking: According to standard, CE-marked, On Termination ID

Finish: Galvanized or Ungalvanized

Standard: EN 12385-4

Fill factor: 0.76

RCN: 23-2

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m	Delivery time
104101006070259	10	1,960	Bright	zZ	90.8	-	SupplierStandard	51.4	7
104101005070259	10	1,960	Bright	sS	90.8	-	SupplierStandard	51.4	7
104101006270259	10	1,960	Galvanized	zZ	90.8	-	SupplierStandard	51.4	7
104101005270259	10	1,960	Galvanized	sS	90.8	-	SupplierStandard	51.4	7
104101006100259	10	2,160	Bright	zZ	95.3	-	SupplierStandard	51.4	7

104101005100259	10	2,160	Bright	sS	95.3	-	SupplierStandard	51.4	7
104101006300259	10	2,160	Galvanized	zZ	95.3	-	SupplierStandard	51.4	7
104101005300259	10	2,160	Galvanized	sS	95.3	-	SupplierStandard	51.4	7
104101106070259	11	1,960	Bright	zZ	109	-	SupplierStandard	61.7	7
104101105070259	11	1,960	Bright	sS	109	-	SupplierStandard	61.7	7
104101106270259	11	1,960	Galvanized	zZ	109	-	SupplierStandard	61.7	7
104101105270259	11	1,960	Galvanized	sS	109	-	SupplierStandard	61.7	7
104101106100259	11	2,160	Bright	zZ	115	-	SupplierStandard	61.7	7
104101105100259	11	2,160	Bright	sS	115	-	SupplierStandard	61.7	7
104101106300259	11	2,160	Galvanized	zZ	115	-	SupplierStandard	61.7	7
104101105300259	11	2,160	Galvanized	sS	115	-	SupplierStandard	61.7	7
104101206070259	12	1,960	Bright	zZ	130	-	SupplierStandard	72.9	7
104101205070259	12	1,960	Bright	sS	130	-	SupplierStandard	72.9	7
104101206270259	12	1,960	Galvanized	zZ	130	-	SupplierStandard	72.9	7
104101205270259	12	1,960	Galvanized	sS	130	-	SupplierStandard	72.9	7
104101206100259	12	2,160	Bright	zZ	137	-	SupplierStandard	72.9	7
104101205100259	12	2,160	Bright	sS	137	-	SupplierStandard	72.9	7
104101206300259	12	2,160	Galvanized	zZ	137	-	SupplierStandard	72.9	7
104101205300259	12	2,160	Galvanized	sS	137	-	SupplierStandard	72.9	7
104101305070259	13	1,960	Bright	sS	153	-	SupplierStandard	84.6	7
104101306270259	13	1,960	Galvanized	zZ	153	-	SupplierStandard	84.6	7
104101305270259	13	1,960	Galvanized	sS	153	-	SupplierStandard	84.6	7
104101306070259	13	1,960	Bright	zZ	153	-	SupplierStandard	84.6	7

104101306100259	13	2,160	Bright	zZ	161	-	SupplierStandard	84.6	7
104101305100259	13	2,160	Bright	sS	161	-	SupplierStandard	84.6	7
104101306300259	13	2,160	Galvanized	zZ	161	-	SupplierStandard	84.6	7
104101305300259	13	2,160	Galvanized	sS	161	-	SupplierStandard	84.6	7
104101406070259	14	1,960	Bright	zZ	179	-	SupplierStandard	97.1	7
104101405070259	14	1,960	Bright	sS	179	-	SupplierStandard	97.1	7
104101406270259	14	1,960	Galvanized	zZ	179	-	SupplierStandard	97.1	7
104101405270259	14	1,960	Galvanized	sS	179	-	SupplierStandard	97.1	7
104101406100259	14	2,160	Bright	zZ	191	-	SupplierStandard	97.1	7
104101405100259	14	2,160	Bright	sS	191	-	SupplierStandard	97.1	7
104101406300259	14	2,160	Galvanized	zZ	191	-	SupplierStandard	97.1	7
104101405300259	14	2,160	Galvanized	sS	191	-	SupplierStandard	97.1	7
104101506070259	15	1,960	Bright	zZ	204	-	SupplierStandard	114	7
104101505070259	15	1,960	Bright	sS	204	-	SupplierStandard	114	7
104101506270259	15	1,960	Galvanized	zZ	204	-	SupplierStandard	114	7
104101505270259	15	1,960	Galvanized	sS	204	-	SupplierStandard	114	7
104101506100259	15	2,160	Bright	zZ	214	-	SupplierStandard	114	7
104101505100259	15	2,160	Bright	sS	214	-	SupplierStandard	114	7
104101506300259	15	2,160	Galvanized	zZ	214	-	SupplierStandard	114	7
104101505300259	15	2,160	Galvanized	sS	214	-	SupplierStandard	114	7
104101606070259	16	1,960	Bright	zZ	232	-	SupplierStandard	130	7
104101605070259	16	1,960	Bright	sS	232	-	SupplierStandard	130	7
104101606270259	16	1,960	Galvanized	zZ	232	-	SupplierStandard	130	7

104101605270259	16	1,960	Galvanized	sS	232	-	SupplierStandard	130	7
104101606100259	16	2,160	Bright	zZ	251	-	SupplierStandard	130	7
104101605100259	16	2,160	Bright	sS	251	-	SupplierStandard	130	7
104101606300259	16	2,160	Galvanized	zZ	251	-	SupplierStandard	130	7
104101605300259	16	2,160	Galvanized	sS	251	-	SupplierStandard	130	7
104101705270259	17	1,960	Galvanized	sS	262	-	SupplierStandard	140	7
104101706070259	17	1,960	Bright	zZ	262	-	SupplierStandard	140	7
104101705070259	17	1,960	Bright	sS	262	-	SupplierStandard	140	7
104101706270259	17	1,960	Galvanized	zZ	262	-	SupplierStandard	140	7
104101705300259	17	2,160	Galvanized	sS	275	-	SupplierStandard	140	7
104101706100259	17	2,160	Bright	zZ	275	-	SupplierStandard	140	7
104101705100259	17	2,160	Bright	sS	275	-	SupplierStandard	140	7
104101706300259	17	2,160	Galvanized	zZ	275	-	SupplierStandard	140	7
104101806070259	18	1,960	Bright	zZ	298	-	SupplierStandard	159	7
104101805070259	18	1,960	Bright	sS	298	-	SupplierStandard	159	7
104101806270259	18	1,960	Galvanized	zZ	298	-	SupplierStandard	159	7
104101805270259	18	1,960	Galvanized	sS	298	-	SupplierStandard	159	7
104101806100259	18	2,160	Bright	zZ	319	-	SupplierStandard	159	7
104101805100259	18	2,160	Bright	sS	319	-	SupplierStandard	159	7
104101806300259	18	2,160	Galvanized	zZ	319	-	SupplierStandard	159	7
104101805300259	18	2,160	Galvanized	sS	319	-	SupplierStandard	159	7
104101906070259	19	1,960	Bright	zZ	331	-	SupplierStandard	178	7
104101905070259	19	1,960	Bright	sS	331	-	SupplierStandard	178	7

104101906270259	19	1,960	Galvanized	zZ	331	-	SupplierStandard	178	7
104101905270259	19	1,960	Galvanized	sS	331	-	SupplierStandard	178	7
104101906100259	19	2,160	Bright	zZ	356	-	SupplierStandard	178	7
104101905100259	19	2,160	Bright	sS	356	-	SupplierStandard	178	7
104101906300259	19	2,160	Galvanized	zZ	356	-	SupplierStandard	178	7
104101905300259	19	2,160	Galvanized	sS	356	-	SupplierStandard	178	7
104102006070259	20	1,960	Bright	zZ	370	-	SupplierStandard	197	7
104102005070259	20	1,960	Bright	sS	370	-	SupplierStandard	197	7
104102006270259	20	1,960	Galvanized	zZ	370	-	SupplierStandard	197	7
104102005270259	20	1,960	Galvanized	sS	370	-	SupplierStandard	197	7
104102006100259	20	2,160	Bright	zZ	397	-	SupplierStandard	197	7
104102005100259	20	2,160	Bright	sS	397	-	SupplierStandard	197	7
104102006300259	20	2,160	Galvanized	zZ	397	-	SupplierStandard	197	7
104102005300259	20	2,160	Galvanized	sS	397	-	SupplierStandard	197	7
104102106070259	21	1,960	Bright	zZ	400	-	SupplierStandard	222	7
104102105070259	21	1,960	Bright	sS	400	-	SupplierStandard	222	7
104102106270259	21	1,960	Galvanized	zZ	400	-	SupplierStandard	222	7
104102105270259	21	1,960	Galvanized	sS	400	-	SupplierStandard	222	7
104102106100259	21	2,160	Bright	zZ	420	-	SupplierStandard	222	7
104102105100259	21	2,160	Bright	sS	420	-	SupplierStandard	222	7
104102106300259	21	2,160	Galvanized	zZ	420	-	SupplierStandard	222	7
104102105300259	21	2,160	Galvanized	sS	420	-	SupplierStandard	222	7
104102205070259	22	1,960	Bright	sS	442	-	SupplierStandard	240	7

104102206270259	22	1,960	Galvanized	zZ	442	-	SupplierStandard	240	7
104102205270259	22	1,960	Galvanized	sS	442	-	SupplierStandard	240	7
104102206070259	22	1,960	Bright	zZ	442	-	SupplierStandard	240	7
104102205100259	22	2,160	Bright	sS	482	-	SupplierStandard	240	7
104102206300259	22	2,160	Galvanized	zZ	482	-	SupplierStandard	240	7
104102205300259	22	2,160	Galvanized	sS	482	-	SupplierStandard	240	7
104102206100259	22	2,160	Bright	zZ	482	-	SupplierStandard	240	7
104102306070259	23	1,960	Bright	zZ	480	-	SupplierStandard	261	7
104102305070259	23	1,960	Bright	sS	480	-	SupplierStandard	261	7
104102306270259	23	1,960	Galvanized	zZ	480	-	SupplierStandard	261	7
104102305270259	23	1,960	Galvanized	sS	480	-	SupplierStandard	261	7
104102306100259	23	2,160	Bright	zZ	504	-	SupplierStandard	261	7
104102305100259	23	2,160	Bright	sS	504	-	SupplierStandard	261	7
104102306300259	23	2,160	Galvanized	zZ	504	-	SupplierStandard	261	7
104102305300259	23	2,160	Galvanized	sS	504	-	SupplierStandard	261	7
104102406070259	24	1,960	Bright	zZ	528	-	SupplierStandard	286	7
104102405070259	24	1,960	Bright	sS	528	-	SupplierStandard	286	7
104102406270259	24	1,960	Galvanized	zZ	528	-	SupplierStandard	286	7
104102405270259	24	1,960	Galvanized	sS	528	-	SupplierStandard	286	7
104102406100259	24	2,160	Bright	zZ	569	-	SupplierStandard	286	7
104102405100259	24	2,160	Bright	sS	569	-	SupplierStandard	286	7
104102406300259	24	2,160	Galvanized	zZ	569	-	SupplierStandard	286	7
104102405300259	24	2,160	Galvanized	sS	569	-	SupplierStandard	286	7

104102506070259	25	1,960	Bright	zZ	568	-	SupplierStandard	312	7
104102505070259	25	1,960	Bright	sS	568	-	SupplierStandard	312	7
104102506270259	25	1,960	Galvanized	zZ	568	-	SupplierStandard	312	7
104102505270259	25	1,960	Galvanized	sS	568	-	SupplierStandard	312	7
104102506100259	25	2,160	Bright	zZ	595	-	SupplierStandard	312	7
104102505100259	25	2,160	Bright	sS	595	-	SupplierStandard	312	7
104102506300259	25	2,160	Galvanized	zZ	595	-	SupplierStandard	312	7
104102505300259	25	2,160	Galvanized	sS	595	-	SupplierStandard	312	7
104102606070259	26	1,960	Bright	zZ	618	-	SupplierStandard	340	7
104102605070259	26	1,960	Bright	sS	618	-	SupplierStandard	340	7
104102606270259	26	1,960	Galvanized	zZ	618	-	SupplierStandard	340	7
104102605270259	26	1,960	Galvanized	sS	618	-	SupplierStandard	340	7
104102605300259	26	2,160	Galvanized	sS	660	-	SupplierStandard	340	7
104102606100259	26	2,160	Bright	zZ	660	-	SupplierStandard	340	7
104102605100259	26	2,160	Bright	sS	660	-	SupplierStandard	340	7
104102606300259	26	2,160	Galvanized	zZ	660	-	SupplierStandard	340	7
104102706070259	27	1,960	Bright	zZ	662	-	SupplierStandard	356	7
104102705070259	27	1,960	Bright	sS	662	-	SupplierStandard	356	7
104102706270259	27	1,960	Galvanized	zZ	662	-	SupplierStandard	356	7
104102705270259	27	1,960	Galvanized	sS	662	-	SupplierStandard	356	7
104102706100259	27	2,160	Bright	zZ	694	-	SupplierStandard	356	7
104102705100259	27	2,160	Bright	sS	694	-	SupplierStandard	356	7
104102706300259	27	2,160	Galvanized	zZ	694	-	SupplierStandard	356	7

104102705300259	27	2,160	Galvanized	sS	694	-	SupplierStandard	356	7
104102806070259	28	1,960	Bright	zZ	712	-	SupplierStandard	391	7
104102805070259	28	1,960	Bright	sS	712	-	SupplierStandard	391	7
104102806270259	28	1,960	Galvanized	zZ	712	-	SupplierStandard	391	7
104102805270259	28	1,960	Galvanized	sS	712	-	SupplierStandard	391	7
104102806100259	28	2,160	Bright	zZ	758	-	SupplierStandard	391	7
104102805100259	28	2,160	Bright	sS	758	-	SupplierStandard	391	7
104102806300259	28	2,160	Galvanized	zZ	758	-	SupplierStandard	391	7
104102805300259	28	2,160	Galvanized	sS	758	-	SupplierStandard	391	7
104102906070259	29	1,960	Bright	zZ	764	-	SupplierStandard	425	7
104102905070259	29	1,960	Bright	sS	764	-	SupplierStandard	425	7
104102906270259	29	1,960	Galvanized	zZ	764	-	SupplierStandard	425	7
104102905270259	29	1,960	Galvanized	sS	764	-	SupplierStandard	425	7
104102906100259	29	2,160	Bright	zZ	801	-	SupplierStandard	425	7
104102905100259	29	2,160	Bright	sS	801	-	SupplierStandard	425	7
104102906300259	29	2,160	Galvanized	zZ	801	-	SupplierStandard	425	7
104102905300259	29	2,160	Galvanized	sS	801	-	SupplierStandard	425	7
104103006070259	30	1,960	Bright	zZ	823	-	SupplierStandard	445	7
104103005070259	30	1,960	Bright	sS	823	-	SupplierStandard	445	7
104103006270259	30	1,960	Galvanized	zZ	823	-	SupplierStandard	445	7
104103005270259	30	1,960	Galvanized	sS	823	-	SupplierStandard	445	7
104103006100259	30	2,160	Bright	zZ	857	-	SupplierStandard	445	7
104103005100259	30	2,160	Bright	sS	857	-	SupplierStandard	445	7

104103006300259	30	2,160	Galvanized	zZ	857	-	SupplierStandard	445	7
104103005300259	30	2,160	Galvanized	sS	857	-	SupplierStandard	445	7
104103206270259	32	1,960	Galvanized	zZ	919	-	SupplierStandard	505	7
104103205270259	32	1,960	Galvanized	sS	919	-	SupplierStandard	505	7
104103206070259	32	1,960	Bright	zZ	919	-	SupplierStandard	505	7
104103205070259	32	1,960	Bright	sS	919	-	SupplierStandard	505	7
104103205100259	32	2,160	Bright	sS	1,008	-	SupplierStandard	505	7
104103206300259	32	2,160	Galvanized	zZ	1,008	-	SupplierStandard	505	7
104103205300259	32	2,160	Galvanized	sS	1,008	-	SupplierStandard	505	7
104103206100259	32	2,160	Bright	zZ	1,008	-	SupplierStandard	505	7
104103406070259	34	1,960	Bright	zZ	1,050	-	SupplierStandard	574	7
104103405070259	34	1,960	Bright	sS	1,050	-	SupplierStandard	574	7
104103406270259	34	1,960	Galvanized	zZ	1,050	-	SupplierStandard	574	7
104103405270259	34	1,960	Galvanized	sS	1,050	-	SupplierStandard	574	7
104103406100259	34	2,160	Bright	zZ	1,151	-	SupplierStandard	574	7
104103405100259	34	2,160	Bright	sS	1,151	-	SupplierStandard	574	7
104103406300259	34	2,160	Galvanized	zZ	1,151	-	SupplierStandard	574	7
104103405300259	34	2,160	Galvanized	sS	1,151	-	SupplierStandard	574	7
104103506070259	35	1,960	Bright	zZ	1,110	-	SupplierStandard	602	7
104103505070259	35	1,960	Bright	sS	1,110	-	SupplierStandard	602	7
104103506270259	35	1,960	Galvanized	zZ	1,110	-	SupplierStandard	602	7
104103505270259	35	1,960	Galvanized	sS	1,110	-	SupplierStandard	602	7
104103506100259	35	2,160	Bright	zZ	1,214	-	SupplierStandard	602	7

104103505100259	35	2,160	Bright	sS	1,214	-	SupplierStandard	602	7
104103506300259	35	2,160	Galvanized	zZ	1,214	-	SupplierStandard	602	7
104103505300259	35	2,160	Galvanized	sS	1,214	-	SupplierStandard	602	7
104103606070259	36	1,960	Bright	zZ	1,170	-	SupplierStandard	644	7
104103605070259	36	1,960	Bright	sS	1,170	-	SupplierStandard	644	7
104103606270259	36	1,960	Galvanized	zZ	1,170	-	SupplierStandard	644	7
104103605270259	36	1,960	Galvanized	sS	1,170	-	SupplierStandard	644	7
104103606100259	36	2,160	Bright	zZ	1,287	-	SupplierStandard	644	7
104103605100259	36	2,160	Bright	sS	1,287	-	SupplierStandard	644	7
104103606300259	36	2,160	Galvanized	zZ	1,287	-	SupplierStandard	644	7
104103605300259	36	2,160	Galvanized	sS	1,287	-	SupplierStandard	644	7
104103806070259	38	1,960	Bright	zZ	1,310	-	SupplierStandard	712	7
104103805070259	38	1,960	Bright	sS	1,310	-	SupplierStandard	712	7
104103806270259	38	1,960	Galvanized	zZ	1,310	-	SupplierStandard	712	7
104103805270259	38	1,960	Galvanized	sS	1,310	-	SupplierStandard	712	7
104103806100259	38	2,160	Bright	zZ	1,444	-	SupplierStandard	712	7
104103805100259	38	2,160	Bright	sS	1,444	-	SupplierStandard	712	7
104103806300259	38	2,160	Galvanized	zZ	1,444	-	SupplierStandard	712	7
104103805300259	38	2,160	Galvanized	sS	1,444	-	SupplierStandard	712	7
104104006070259	40	1,960	Bright	zZ	1,450	-	SupplierStandard	807	7
104104005070259	40	1,960	Bright	sS	1,450	-	SupplierStandard	807	7
104104006270259	40	1,960	Galvanized	zZ	1,450	-	SupplierStandard	807	7
104104005270259	40	1,960	Galvanized	sS	1,450	-	SupplierStandard	807	7

104104006100259	40	2,160	Bright	zZ	1,590	-	SupplierStandard	807	7
104104005100259	40	2,160	Bright	sS	1,590	-	SupplierStandard	807	7
104104006300259	40	2,160	Galvanized	zZ	1,590	-	SupplierStandard	807	7
104104005300259	40	2,160	Galvanized	sS	1,590	-	SupplierStandard	807	7
104104206070259	42	1,960	Bright	zZ	1,600	-	SupplierStandard	884	7
104104205070259	42	1,960	Bright	sS	1,600	-	SupplierStandard	884	7
104104206270259	42	1,960	Galvanized	zZ	1,600	-	SupplierStandard	884	7
104104205270259	42	1,960	Galvanized	sS	1,600	-	SupplierStandard	884	7
104104206100259	42	2,160	Bright	zZ	1,758	-	SupplierStandard	884	7
104104205100259	42	2,160	Bright	sS	1,758	-	SupplierStandard	884	7
104104206300259	42	2,160	Galvanized	zZ	1,758	-	SupplierStandard	884	7
104104205300259	42	2,160	Galvanized	sS	1,758	-	SupplierStandard	884	7
104104406070259	44	1,960	Bright	zZ	1,750	-	SupplierStandard	961	7
104104405070259	44	1,960	Bright	sS	1,750	-	SupplierStandard	961	7
104104406270259	44	1,960	Galvanized	zZ	1,750	-	SupplierStandard	961	7
104104405270259	44	1,960	Galvanized	sS	1,750	-	SupplierStandard	961	7
104104406100259	44	2,160	Bright	zZ	1,925	-	SupplierStandard	961	7
104104405100259	44	2,160	Bright	sS	1,925	-	SupplierStandard	961	7
104104406300259	44	2,160	Galvanized	zZ	1,925	-	SupplierStandard	961	7
104104405300259	44	2,160	Galvanized	sS	1,925	-	SupplierStandard	961	7
104104606070259	46	1,960	Bright	zZ	1,920	-	SupplierStandard	1,060	7
104104605070259	46	1,960	Bright	sS	1,920	-	SupplierStandard	1,060	7
104104606270259	46	1,960	Galvanized	zZ	1,920	-	SupplierStandard	1,060	7

104104605270259	46	1,960	Galvanized	sS	1,920	-	SupplierStandard	1,060	7
104104606100259	46	2,160	Bright	zZ	-	-	SupplierStandard	1,060	7
104104605100259	46	2,160	Bright	sS	-	-	SupplierStandard	1,060	7
104104606300259	46	2,160	Galvanized	zZ	-	-	SupplierStandard	1,060	7
104104605300259	46	2,160	Galvanized	sS	-	-	SupplierStandard	1,060	7
104104806270259	48	1,960	Galvanized	zZ	2,090	-	SupplierStandard	1,150	7
104104805270259	48	1,960	Galvanized	sS	2,090	-	SupplierStandard	1,150	7
104104806070259	48	1,960	Bright	zZ	2,090	-	SupplierStandard	1,150	7
104104805070259	48	1,960	Bright	sS	2,090	-	SupplierStandard	1,150	7
104104806300259	48	2,160	Galvanized	zZ	-	-	SupplierStandard	1,150	7
104104805300259	48	2,160	Galvanized	sS	-	-	SupplierStandard	1,150	7
104104806100259	48	2,160	Bright	zZ	-	-	SupplierStandard	1,150	7
104104805100259	48	2,160	Bright	sS	-	-	SupplierStandard	1,150	7
104105006070259	50	1,960	Bright	zZ	2,270	-	SupplierStandard	1,230	7
104105005070259	50	1,960	Bright	sS	2,270	-	SupplierStandard	1,230	7
104105006270259	50	1,960	Galvanized	zZ	2,270	-	SupplierStandard	1,230	7
104105005270259	50	1,960	Galvanized	sS	2,270	-	SupplierStandard	1,230	7
104105006100259	50	2,160	Bright	zZ	-	-	SupplierStandard	1,230	7
104105005100259	50	2,160	Bright	sS	-	-	SupplierStandard	1,230	7
104105006300259	50	2,160	Galvanized	zZ	-	-	SupplierStandard	1,230	7
104105005300259	50	2,160	Galvanized	sS	-	-	SupplierStandard	1,230	7