

## Eye sling hook with latch, grade 80



### Product information

Hook is equipped with spring loaded safety latch.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-2

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

Part Code	WLL ton	EWL mm	For chain dia. mm	K mm	E mm	F mm	R mm	A mm	Weight kg	Delivery time
401300110680	1.12	76	6	108	24	9	21	20	0.3	7
401300200680	2	90	7/8	133	30	11	26	25	0.4	7
401300320680	3.15	117	10	167	34	15	39	38	0.9	7
401300530680	5.3	152	13	213	39	19	54	43	1.7	7
401300800680	8	178	16	255	46	23	64	50	3.2	7
401301250680	12.5	226	20	305	40	24	80	62	5.8	3
401301500680	15	249	22	348	71	32	80	62	8.5	7
401303150680	31.5	346	32	480	102	37	112	68	17	7

## Technical data

### SPARE PARTS

Spare part set (product code)   Inc. latch, spring and pin/nut	Fits the hook (product code)
SALKVO6S	SALK6
SALKVO78S	SALK78
SALKVO10S	SALK10
SALKVO13S	SALK13
SALKVO16S	SALK16
SALKVO20S	SALK20
SALKVO22S	SALK22
SALKVO26S	SALK26
SALKVO32S	SALK32

# Blueprint

