



## Master link, grade 80

### Product information

Masterlink for chain sling assemblies.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

Part Code	WLL ton	EWL mm	For chain mm, 1-leg	For chain mm, 2-leg	A mm	B mm	D mm	Weight kg	Delivery time
401100160260	1.6	110	6/7	6	110	60	13	0.34	3
401100210260	2.12	110	8	7	110	60	16	0.53	3
401100320260	3.15	135	10	8	135	75	18	0.8	3
401100530260	5.3	160	13	10	160	90	22	1.5	3
401100800260	8	180	16	13	180	100	26	2.3	3
401101120260	11.2	200	18	16	200	110	32	3.9	3
401101400260	14	260	20	18	260	140	36	6.35	3
401101700260	17	300	22	20	300	160	40	9	3
401102120260	21.2	340	26	22	340	180	45	12.8	7
401103150260	31.5	350	32	26	350	190	50	17.2	7
401104500260	45	400	36	32	400	200	56	24.2	7

## Blueprint

