



## Swivel

### Product information

**General:** Swivels are essential for the safe and efficient installations of cables, both over and underground. Ball bearing swivels stop torque gradually building by both the pulling equipment and the lay of the cables themselves. The swivels are contoured to allow ease of passage through pulley sheaves. Swivels are an indispensable aid for safe and easy cable laying. The use of double axial bearings makes it possible to neutralise the torsion as required, even under maximum tension.

**Material:** Stainless steel. Variant with BF 66.7 kN Alloy Steel

Part Code	Min. Breaking force kN	Clevis gap mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg	Delivery time
492506400060	10	7,1	16	7.1	4.8	17.5	6.4	51	64	0.06	7
492507800060	15	7,1	20	7.1	4.8	22.6	8.7	61	78	0.12	7
492508600060	30	9,5	22	9.5	7.9	24.6	11.1	64	86	0.15	7
492509500060	46.7	10,3	25	10.3	9.5	27.8	12.7	73	98	0.23	3
492512100060	66.7	13,5	32	13.5	10.3	32.5	13.5	94	121	0.45	7
492513000060	93.4	14,3	35	14.3	12.7	35	15.9	98	130	0.63	3
492515240060	133.4	17,5	41	17.5	15.9	43.7	19.1	114	152	0.95	3
492517800060	200.1	19,8	51	19.8	17.5	52.4	23.8	130	178	1.7	7
492525400060	330	26,2	60	26.2	22.2	70.6	30.2	202	262	3.5	7
492533000060	667	30,2	76	20.2	28.6	98	44	260	349	7.7	7

# Blueprint

