



Lifting Eye FP

Product information

Enormously flat lifting eye.

- The eyes can be loaded with working load limit in all directions and rotates 360°.
- Automatic locking link when folded.
- Secured four times against breakage in all load directions.
- Admissible working range of take-up link 110°.

Material: Eye and swivel of alloy steel.

Marking: WLL.

Finish: Painted.

Note: The surface that the lifting eyes shall be attached to shall be flat and tolerate the load it is going to be exposed to.

Safety factor: 4:1

Part Code	Code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	Ø d mm	E mm	F mm	G mm	I mm	Øs mm	Weight kg	Delivery time
42150381100000	FP 0.5	0.5	M10	60	69	50	48	13	28	100	12	52	34	0.71	7
42150381101000	FP 0.8	0.8	M12	90	69	50	48	13	28	100	17	51	34	0.73	7
42150381101500	FP 1.5	1.5	M16	160	69	50	48	13	28	100	27	49	34	0.77	7
42150381102100	FP 2.5	2.5	M20	420	69	50	48	13	33	103	37	44	41	0.92	7
42150381104200	FP 4-S	4	M24	750	69	50	48	13	34	103	46	40	41	1.05	7
42150381104000	FP 4	4	M24	750	104	76	78	18	39	147	41	74	58	2.5	7
42150381105000	FP 5	5	M27	1,000	104	76	72	18	39	147	51	72	58	2.63	7
42150381106000	FP 6	6	M30	1,400	104	76	72	18	39	147	51	70	58	2.74	7
42150381108000	FP 8	8	M36	1,800	104	76	72	18	43	147	57	62	58	3.15	7

Technical data

WLL (ton)

	<input type="text"/>	<input type="text"/>	<input type="text"/>
FP-0,5	0.7	0.5	0.7
FP-0,8	1.25	0.8	1.12
FP-1,5	2.12	1.5	2
FP-2,5	3.55	2.5	3.35
FP-4S	4	4	5.6
FP-4	5.6	4	5.6
FP-5	7.1	5.3	7.1
FP-6	8	6	8
FP-8	8	8	11.2

Blueprint

