




Open Wedge Socket OWS

Product information



Intended for attaching of wire rope where switching often occur, e.g. blocks of mobilecranes, or to be able to adjust the length of the wire rope. See recommended assembly to get correct results.

Design: The wedge socket is delivered complete.

Marking house and wedge: Wire \varnothing mm.

The dead end should have a length of 6 times the wire dia. with a minimum of 150mm.

Material: Cast alloy steel with high mechanical properties.

Finish: Blue painted or hot dip galvanized (OWS 0.25 to 0.5 is standard delivered with galvanized finish) / Pin or bolt.

Note: The efficiency of a 6 and 8 strand wire rope/wedge socket connection is 80% of the minimum breaking load of the wire but limited to the minimum breaking load of the socket (MBL).

Part Code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø P mm	T mm	W mm	TL mm	TB mm	Weight kg	Delivery time
121500800152	OWS 0,25 P	7-8	8	Galvanized	110	18	36	16	9	18	128	51	0.8	7
121501000152	OWS 0,5 P	9-10	12	Galvanized	145	23	46	21	11	21	165	63	1.7	7
121501300152	OWS 1 P	11-13	20	Galvanized	146	28,5	57	25	12	25	174,5	67	2.1	7
121501600152	OWS 2 P	14-16	25	Galvanized	176	35	70	30	15	31	211	85	4	7
121501900152	OWS 3 P	18-19	40	Galvanized	210	40	80	35	16	38	250	95	7	7
121502200152	OWS 4 P	20-22	55	Galvanized	237,5	47,5	95	41	18	44	285	110	10	7
121502600152	OWS 5 P	24-26	75	Galvanized	275	55	110	51	22	51	330	128	15	7
121502900152	OWS 6 P	27-29	90	Galvanized	310	65	130	57	25	57	375	142	21	7
121503200152	OWS 7 P	30-32	110	Galvanized	350	73	146	64	28	63	423	155	31	7
121503600152	OWS 8 P	34-36	125	Galvanized	400	74	148	64	28	70	474	160	37	7
121503900152	OWS 9 P	37-39	150	Galvanized	450	80	142	70	30	77	530	177	51	7
121504200152	OWS 10 P	40-42	170	Galvanized	500	87	160	76	33	76	587	187	64	7
121504800152	OWS 11 P	43-48	225	Galvanized	550	100	186	89	39	89	650	215	96	7
121505200152	OWS 12 P	49-52	280	Galvanized	640	105	205	95	46	101	745	244	130	7
121505800152	OWS 13 P	54-58	360	Galvanized	660	125	250	108	54	114	785	275	180	7
121506800152	OWS 14 P	60-68	425	Galvanized	835	135	270	121	60	127	970	300	275	7
121507600152	OWS 15 P	72-76	460	Galvanized	1,000	150	300	133	76	146	1,150	355	440	7
121508600152	OWS 16 P	81-86	625	Galvanized	1,100	150	300	140	79	159	1,250	375	510	7

Blueprint

