



Green Pin tropiseekel P-6033

Tootekirjeldus

General: Bow shackles with safety bolt.

Temperature range: -20°C up to +200°C.

Certification: At no extra charges this product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity and all shackles from 75 t and up are supplied with a Lloyd's Register of Shipping Certificate on proof load. For shackles 75 t and up an MPI and/or US inspection certificate can be supplied on request.

Materjal: Bow and pin alloy steel, Grade 8, quenched and tempered.

Märgistus: CE-tähisega

Pinnakate: Shackle bow painted silver, pin painted green.

Märkus: for details on dimensions and tolerances please consult our CAD drawings, these are available on request.

Ohutustegur: 5:1

Klass: 8

Tootekood	WLL tonn	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	l mm	Kaal kg	Tarneaeg
420100701010	7	22	22	46	19	32	96	64	153	115	110	19	41	1,97	7
420101251010	12,5	28	28	61	25	44	120	82	197	151	146	24	54	4,27	7
420101801010	18	35	35	69	30	54	148	102	239	171	180	29	64	6,85	7
420103001010	30	40	42	90	35	69	165	126	279	207	200	34	79	12,5	7
420104001010	40	55	51	109	45	84	199	140	331	252	235	38	97	20,3	7
420105501010	55	60	57	115	55	90	240	160	389	294	270	45	100	30,4	7
420107501010	75	68	70	126	54	110	290	185	473	317	331	40	120	49	7
420112501010	125	85	80	156	85	137	366	220	583	413	390	40	150	95	7
420115001010	150	94	95	181	89	147	391	253	648	445	449	50	170	125	7
420120001010	200	110	105	201	100	158	481	280	759	480	500	50	205	190	7
420125001010	250	126	120	229	110	179	542	300	860	535	552	60	240	264	7
420130001010	300	136	134	246	134	195	601	350	946	590	620	70	265	360	7
420140001010	400	160	160	295	145	231	576	370	995	687	710	80	320	583	7
420150001010	500	170	180	330	160	263	681	450	1 161	762	850	90	340	862	7
420160001010	600	190	200	360	170	289	741	490	1 264	827	930	100	370	1 134	7
420170001010	700	200	215	392	190	315	751	540	1 284	879	901	100	400	1 360	7
420180001010	800	218	230	420	200	342	851	554	1 426	942	947	110	420	1 680	7
420190001010	900	242	255	466	220	368	851	580	1 488	1 023	1 023	120	440	1 650	7
420110001011	1 000	260	270	490	240	399	851	614	1 532	1 103	1 107	120	460	2 970	7
420112501011	1 250	285	300	510	260	452	931	650	1 666	1 227	1 182	150	530	3 700	7
420115501011	1 550	285	320	550	280	483	950	680	1 710	1 300	1 253	150	560	4 000	7

Blueprint

