



Green Pin tõsteseekel G-4153

Tootekirjeldus

- **General:** Dee shackle with safety bolt.

- **Temperature range:** -40°C up to +200°C.

- **Finish:** Hot dipped galvanized.

- **Certification:** At no extra charges this product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

Materjal: Bow and pin high tensile steel, Grade 6, quenched and tempered.

Märgistus: Vastavalt standardile, CE-tähisega

Standard: EN 13889

Ohutustegur: 6:1

Klass: 6

Tootekood	WLL tonn	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	Kaal kg	Tarneaeg
420100200560	2	13,5	16	34	13	22	43	81	82	13	0,39	3
420100330560	3,25	16	19	40	16	27	51	97	98	17	0,67	7
420100480560	4,75	19	22	46	19	31	59	112	114	19	1,08	3
420100650560	6,5	22	25	52	22	36	73	134	130	22	1,66	7
420100850560	8,5	25	28	59	25	43	85	154	150	25	2,46	7
420100950560	9,5	28	32	66	28	47	90	167	166	27	3,4	7
420101200560	12	32	35	72	32	51	94	180	178	30	4,51	3
420101350560	13,5	35	38	80	35	57	115	209	197	33	6,1	7
420101700560	17	38	42	88	38	60	127	230	202	19	7,63	7
420102500560	25	45	50	103	45	74	149	271	249	23	12,88	7
420103500560	35	50	57	111	50	83	171	305	269	26	17,35	7
420104250560	42,5	57	65	130	57	95	190	345	301	29	25,94	7
420105500560	55	65	70	145	65	105	203	376	330	32	35,33	7
420108500560	85	75	83	162	73	127	229	427	380	39	52,97	7

Blueprint

