



## Green Pin tõsteseekel G-4151

### Tootekirjeldus

- **General:** Dee shackle with screw collar pin.

- **Standard:** EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVB Class 2, Grade A.

- **Temperature range:** -40°C up to +200°C.

- **Certification:** At no extra charges this product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

**Materjal:** Bow and pin high tensile steel, Grade 6, quenched and tempered.

**Märgistus:** Vastavalt standardile, CE-tähisega

**Pinnakate:** Hot dipped galvanized.

**Standard:** EN 13889

**Ohutustegur:** 6:1

**Klass:** 6

<b>Tootekood</b>	<b>WLL tonn</b>	<b>A mm</b>	<b>B mm</b>	<b>C mm</b>	<b>D mm</b>	<b>e mm</b>	<b>f mm</b>	<b>g mm</b>	<b>h mm</b>	<b>Kaal kg</b>	<b>Tarneaeeg</b>
420100030680	0,33	5	6	12	5	9,5	19	33	29,5	0,02	7
420100050680	0,5	7	8	16,5	7	12	22	41,5	38	0,05	7
420100080680	0,75	9	10	20	9	13,5	26	50	46,5	0,09	7
420100100680	1	10	11	22,5	10	17	32	59	54	0,14	7
420100150680	1,5	11	13	26,5	11	19	37	68	59,5	0,19	7
420100200680	2	13,5	16	34	13	22	43	81	73	0,32	7
420100330680	3,25	16	19	40	16	27	51	97	89	0,54	7
420100480680	4,75	19	22	46	19	31	59	112	103	0,87	7
420100650680	6,5	22	25	52	22	36	73	134	119	1,34	7
420100850680	8,5	25	28	59	25	43	85	154	137	2,08	7
420100950680	9,5	28	32	66	28	47	90	167	153	2,77	7
420101200680	12	32	35	72	32	51	94	180	170	3,72	7
420101350680	13,5	35	38	80	35	57	115	209	186	5,14	3
420101700680	17	38	42	88	38	60	127	230	203	6,85	7
420102500680	25	45	50	103	45	74	149	271	243	11,45	7
420103500680	35	50	57	111	50	83	171	305	272	16,86	7
420104250680	42,5	57	65	130	57	95	190	345	310	24,61	7
420105500680	55	65	70	145	65	105	203	376	344	32,65	7

# Blueprint

