

Anchor Point ABS - Lock X-Rivet

Tootekirjeldus



Anchorage point - designed for riveting onto sandwich and trapezoidal sheeting.
Anchor point ABS-Lock X-Rivet is simply riveted on top of roof membrane using 14 watertight blind rivets.

The 2 different base plates can be used for different seam intervals.

- LX-SW-N-250 -> Distance between the holes: 180-250 mm
- LX-SW-N-333 -> Distance between the holes: 280-333 mm

Also available as an intermediate ("ZW") bracket in a lifeline system in 2 heights.

- LX-SW-N-...-ZW -> Bracket height 150 mm
- LX-SW-N-...-ZW-350 -> Bracket height 350 mm

For steel plating: ≥ 0.45 mm;
Aluminium: ≥ 0.8 mm.

Force directions: Lateral.

Substructure: Sandwich, trapezoidal sheeting, profile roof.

Attachment: Riveted

Application: Profile Roof, flat roofs

Märgistus: Vastavalt standardile

Standard: EN 795, CEN/TS/16415

Tootekood	Kood	Max. number of persons	Kaal kg	Tarneaeg
8415LXSWN250	19.10LX-SW-N-250	3	2,012	7
8415LXSWN333	19.10LX-SW-N-333	3	2,129	7
8415LXSWN250ZW	19.10LX-SW-N-250-ZW	3	2,34	7
8415LXSWN333ZW	19.10LX-SW-N-333-ZW	3	2,457	7
8415LXSWN250ZW350	19.10LX-SW-N-250-ZW-350	3	2,712	7
8415LXSWN333ZW350	19.10LX-SW-N-333-ZW-350	3	2,829	7