



## KITO elektriline kett-tali tüüp ER2, ühe kiirusega

### Tootekirjeldus

#### Electric chain hoist with hook suspension

**General:** The ER2 Electric Chain Hoists are durable, safe and easy to use hoists. It has a top hook or overhead mounting suspension, aluminium die-cast body, electromagnetic brake and a canvas chain container. It lifts from 10 tons up to 20 tons.

#### Standard configuration:

- 400 V/50 Hz
- Contactor control for single speed
- CH-Meter: operating hours/number of starts
- Ergonomic push button control
- Upper-lower limit switch
- Nickel-plated load chain class grade 80 (DAT) in accordance with Norm EN 818-7
- Thermal protector
- Carbon friction clutch > 400 V/50 Hz

#### Options:

- 500 V/Contactor control
- 230 V/50 Hz/60 Hz, 3 phase
- Rubber bumpers for motorized trolleys
- Additional mechanical brake
- Electrical overload limiter
- Acoustic overload signal
- Radio remote control
- Variable speed control
- Level limit switch
- Steel chain container
- Trolley versions: motorized, geared and plain

Kood	WLL	Keti languste arv	Testkoormus (tonn)	Lifting motor Output (kW)	Lifting motor Rating (%ED)	Tõstekiirus* (m/min)	50HzISO/FEM klass	Lisakaal 1m tõstekõrguse kohta	Tõstekett	Kaal	Tarneaeg
tonn								mm	mm	kg	
ER2-1005	10	4	12,5	3,5x2	60	2,9	M4/1Am	11	11,2 x 31,3	303	7
ER2-1505	15	6	18,8	3,5x2	60	1,9	M4/1Am	17	11,2 x 31,3	404	7
ER2-2005	20	8	25,0	3,5x2	60	1,4	M4/1Am	22	11,2 x 31,3	476	7

## Tehnilised andmed

WLL	Kood	Min. kõrgus C	D	a	b	w	g
tonn		mm	mm	mm	mm	mm	mm
10	ER2-100S	1370	1210	798	849	956	80
15	ER2-150S	1595	1520	798	1022	1129	86
20	ER2-200S	1710	1600	798	1198	1305	102

# Blueprint

