



Tõstesilm tüüp PLGW-SN G10

Tootekirjeldus

General: A revolutionary lifting eye which, thanks to the patented system with the red latches (see images) can be mounted by hand (latches in the upright position) and then freely rotate 360° around its own axis after installation (latches in the down position). The eye can be loaded within a range of 180°. The eye can be used individually or in combination with multiple eyes and should be tightened only by hand. This version of PLGW is used in those areas where a threaded bolt on the load is used instead of a simple thread. There is also the possibility to mount the lifting point PLGW-SN with a commercially available (standard) screw through the clearance hole. The benefit with the eye nut is that no matter the width of the load, the same lifting points can be used. All you need are standard screws with different screw lengths.

Standard: EN 1677-1, DIN ISO 9001.

Materjal: Alloy steel grade 10.

Märgistus: Vastavalt standardile, CE-tähisega, WLL, and an individual serial number.

Pinnakate: Painted.

Standard: EN 1677-1
except grade/WLL

Ohutustegur: 4:1

Tootekood	Kood	WLL tonn	Thread mm	a mm	b mm	c mm	d mm	e mm	f mm	Kaal kg	Tarneaeg
42158441	PLGW-SN 0,3 t	0,3	M8	25	45	10	21	55	35	0,17	7
42158449	PLGW-SN 0,5 t	0,5	M10	25	45	10	21	55	35	0,17	7
421598428	PLGW-SN 0,7 t	0,7	M12	30	55	12	25	65	43	0,28	7
421598783	PLGW-SN 1,5 t	1,5	M16	35	64	14	29	72	50	0,42	7
421598784	PLGW-SN 2,3 t	2,3	M20	40	69	16	34	80	54	0,5	7
421598785	PLGW-SN 3,5 t	3,5	M24	50	86	18	40	95	69	1	7
42158454	PLGW-SN 4,9 t	4,9	M30	60	110	25	47	115	90	2	7

Tehnilised andmed

Tõsteviis	□	□	□	□	□	□	□	□	□	□	□	
	Tõstepunktide arv	1	1	2	2	2	2	3+4	3+4	2	3+4	
	Tõstenurk	0°	90°	0°	90°	0°-45°	45°-60°	0°-45°	45°-60°	ebasüm.	ebasüm.	
Kood	Keere	WLL (t)	mm									
PLGW-SN 0,3 t	M8	1,0	0,3	2,0	0,6	0,4	0,3	0,6	0,4	0,3	0,3	12
PLGW-SN 0,5 t	M10	1,5	0,5	3,0	1	0,7	0,5	1	0,7	0,5	0,5	12
PLGW-SN 0,7 t	M12	2	0,7	4	1,4	1	0,7	1,4	1	0,7	0,7	14
PLGW-SN 1,5 t	M16	4	1,5	8	3	2,1	1,5	3	2,2	1,5	1,5	19
PLGW-SN 2,3 t	M20	5	2,3	10	4,6	3,2	2,3	4,8	3,4	2,3	2,3	22
PLGW-SN 3,5 t	M24	6,5	3,5	13	7	4,9	3,5	7,4	5,2	3,5	3,5	27
PLGW-SN 4,9 t*	M30	12	4,9	24	9	6,9	4,9	10,3	7,3	4,9	4,9	36

Blueprint

